



Town of Walden

ROAD CUT APPLICATION

Remit application and fee to:

Town of Walden

1836 Taft Highway

Walden, Tennessee 37377

APPLICATION MUST BE LEGIBLE AND FILLED OUT COMPLETELY.

UTILITY COMPANIES, PLEASE CONTACT THE OFFICE FOR POSSIBLE FEE WAIVER.

APPLICANT INFORMATION (Please Print)

Date	Name		
Street Address		State	Zip Code
Phone Number	Email Address	Applicant Signature	

COMPANY INFORMATION (Please Print)

Name		Phone Number	
Street Address		State	Zip Code
Project Supervisor		Phone Number	

PROJECT INFORMATION (Please Print)

Date Work to Begin	Estimated Date of Complete Restoration
Street Address/Location of Cut	

REQUIRED ATTACHMENTS

- Permit Fee: \$20.00
- Map of the cut or bore location
- (Make checks payable to Town of Walden)
- Certificate of Insurance
- Approved bond
- Traffic management plan

See page 2 for Specifications for Road Cut Repairs
For questions email info@waldentn.gov or call 423-886-4362

BELOW FOR OFFICE USE ONLY

Approved by Town Administrator

Date

Total Fees	Date Paid	Check No	Staff



Town of Walden

ROAD CUT APPLICATION

SPECIFICATIONS FOR ROAD CUT REPAIRS

For hot mix roads – asphalt or concrete:

1. Authorized cuts to be made with a saw.
2. Cuts to have straight edges and square corners.
3. Ditch to be filled with compacted 33 P or 33 C gravel.
4. Minimum of 4" thick concrete which extends a minimum of 8" past filled area onto solid undisturbed ground.
5. Minimum of 2" asphaltic concrete blend with top of existing road surface.
6. Crack to be filled with asphalt crack sealer.

For chip-sealed roads:

1. Ditch to be filled with compacted 33 P or 33 C gravel.
2. Surface to be repaired with either:
 - a. Hot asphaltic concrete mix (2")
 - b. Cold asphaltic concrete mix (2")
 - c. Double layer of chip seal (2")

For road shoulders:

1. Ditch to be filled with compacted 33 P or 33 C gravel.
2. Surface to be repaired to match existing shoulder surface. This could be asphaltic cement, chip seal, or compacted soil with grass. Existing grass shoulders should be stabilized with permanent vegetation. Mulch is required for all permanent vegetation application. Mulch applied to seeded areas shall achieve 75% soil cover.

For roadside drainage ditches:

1. Utility ditch to be filled with compacted 33 P or 33 C gravel.
2. In steep areas where erosion is a problem, it may be necessary to fill with large stone (10"-14").